


Advantage Mono Compiler

Creates a mono Audio Description WAV file from an ESEF file

Advantage Mono Compiler is a software application that processes an ESEF file and creates an output file that contains the mono Audio Description commentary.

The output WAV file consists of a mono commentary WAV on the left channel of a locked stereo pair, the right channel is left silent.



Key features

- User friendly interface
- Creates a stereo pair with the right channel silent, or a single mono WAV file, suitable for manually controlled mixing
- Auto check on input file timecode validity – checks for overlapping timecode on AD file
- Add or edit BWA header file during output file creation

PC requirements

Operating system - Microsoft Windows 7 or Windows 2008 R2 server.

The PC hardware should have the following minimum specification:
3 GHz Pentium class processor, 1GB RAM and Windows Media player 9 or above installed.

Licensing

The application is protected by means of a hardware security dongle. In multiple system networked environments a central server licensing model is used to distribute licences as required.

Associated products

Advantage Mono Compiler is one of a family of Audio Description products available from Starfish Technologies Ltd. Together these products can be configured to create complete AD workflow solutions. Please see www.starfish.tv for more details.

ESEF Files

ESEF is a widely used broadcast standard interchange file format for Audio Description, and is the required source file format for the Advantage Compiler products.

An ESEF file sets consist of an .esf file and a set of individual WAV files associated with each description.

The .esf file contains - script data for each description, in-time and out-time timecodes of each description, the filename of the WAV file for each associated description - not the actual audio recording itself, the fade duration, fade depth and stereo pan data for each description.

The recommended fade depths for broadcast use are: 1/3 dB, 3 dB, 6 dB, 9 dB, 12 dB, 15 dB, 18 dB, 21 dB, "Maximum" i.e. no programme sound audible at all.

The recommended fade durations for broadcast use are: 0 frames, 3 frames, 10 frames, 25 frames.

All specifications and minimum requirements are subject to change without prior notice. Please check before purchase.